

Spectralink DECT Base Station

Over the air signaling between the Spectralink DECT Server 2500 and 8000 and Spectralink 7000 Series Handsets



The Spectralink DECT Base Station controls the traffic channels in the air and functions as the link between Spectralink 7000 Series handsets and the Spectralink DECT Server.

The Spectralink DECT Server powers the Spectralink DECT Base Station via a standard twisted pair cable. Each Spectralink DECT Base Station requires only one pair, which can be up to 2,000 meters (6562 feet).

Each Spectralink DECT Base Station covers a circular area between 50 and 600 meters (164 to 1968 feet). The size of the coverage area depends on location specifics such as building materials. Before installation, each location needs to be assessed to define the number of Spectralink DECT Base Stations required to achieve desired coverage.

The Spectralink DECT Base Station is used with the Spectralink DECT Server 2500 and 8000.

SPECIFICATIONS

SYSTEM CAPACITY WITHOUT EXTERNAL ANTENNA

- Max. number of speech channels: four

RADIO INTERFACE

- Average transmit power: typical 5mW/ch. (US), 10mW/ch. (EU)
- Peak transmit power: typical 125mW (US), 250mW (EU)
- Receiver sensitivity: typical -90 dBm.
- Typical range (circular coverage area):
 - indoor: 65.6 - 164 ft. (20-50 m.)
 - outdoor: up to 1967 ft. (600 m.)

RADIO APPROVALS

- EN 301 406
- FCC RULES PART 15/Subpart D, RSS-213

ELECTRO MAGNETIC COMPATIBILITY (EMC) APPROVALS (REGULATORY STANDARDS)

- EN 301 489-1
- EN 301 489-6

SAFETY (REGULATORY STANDARDS)

- UL60950-1 CAN/CSA-C22.2 No. 60950-1-03
- EN 60950-1+ A11

ENVIRONMENTAL CONDITIONS

- Operating temperature: 14 - 131° F (-10 - 55° C)
- Storage temperature: Not tested
- Relative humidity: Between 20% and 80% (non-condensing)
- The equipment is in compliance with the requirements of EU directive 2002/95/EC (ROHS) and 2002/96/EC (WEEE)

ELECTRICAL REQUIREMENTS

- Power consumption: 0.98W (Max. 1.23W)
- The power supply is 48 VDC, 21mA (Powered via the server)

PHYSICAL CHARACTERISTICS

- Size: 3.9 x 1.2 x 3.9 in. (100 x 30 x 100 mm.)
- Weight: 4 oz. (113 gr.)
- Grey-white (NCS 0502-Y)
- Wall-mountable, indoor

AVAILABILITY

- The Spectralink DECT Base Station is globally available, and is regulatory certified for frequency bands used in North America, Europe, and Australia.

Learn More

Learn what Spectralink wireless telephones can do for your organization. Visit us at spectralink.com or contact your Spectralink representative.

spectralink.com
info@spectralink.com
+1 800-775-5330 North America
+45 7560 2850 EMEA