



DESCRIPTION

SMART1 has a future-proof and open platform, which allows you to use your own apps and features. Some great benefits are listed below:

- With your own applications, you will be unique on the market
- Tailored to be used as a working tool – durable and secure
- High recognition factor
- Less attractive to thieves than a standard mobile phone
- Easy replaceable battery – 24/7
- Attractive ROI and economic lifecycle

Differences from standard smartphones

- Alarm button
- Extra feature key (PTT/Assistance)
- Physical buttons
- Top Display
- Belt clip
- Rubber details protects against damage, provide a better grip and keep the phone in place

TECHNICAL DATA

| | |
|----------------------------|--|
| OS: | Android |
| Processor: | iMX6 dual Core |
| Memory: | 4GB Flash, 1GB RAM, Micro SDHC <64GB |
| Front display: | 4" IPS TFT (480x800), 16M colors, Touchscreen, LCD backlight, Dragontrail glass. |
| Top Display: | Monochrome, OLED |
| Camera: | 5M pixel rear camera, 1600x1200 pixels |
| HAC | (Hearing Aid) Compatible |
| Sensors: | 3-axis accelerometer, proximity, light sensor |
| Language: | 14 |
| Size: | 135x66x15mm. |
| Weight: | 195g |
| Color: | Light grey |
| Battery: | 1600mA Li-Ion |
| IP-class: | IP-54 |
| Bacterial: | Disinfections resistant |
| Buttons: | Alarm Button, Pre-Alarm, PTT (PushToTalk), Vol +/-, On/off hook, Home, Back. |
| Advanced Messaging: | Compatible with CMS COBS Messaging Server). |

| | |
|------------------------|---|
| Talk Time: | 16 Hours (DECT only), 10 Hours (WiFi only) |
| Standby: | 160 Hours (WiFi & BT off) |
| DECT: | Europe, Latin America, US <ul style="list-style-type: none"> • 4 power levels (ECO mode) • DECT automatic encryption for call security • GAP, 6.0 and CAT-iq • PTT (Push To Talk) |
| WiFi: | 802.11 a/b/g/n |
| Security: | WEP, TKIP, AES, WAPI |
| Authentication: | 802.1x, WPA, WPA-2, WPA-2 PSK |
| QoS: | VMM |
| Cisco Support: | CCX4, CCX lite |
| AUDIO: | G.711, G.722, G.726, HD Audio, Speakerphone |
| NFC | |
| Bluetooth: | Bluetooth 4 (BLE) |
| Approvals: | EN301 489-1, EN301489-6, EN301489-17, EN300440-1, EN3000440-2, EN50360, EN301406, EN300328, EN301893, EN300328, EN60950-1 |